



# *AQF - 500 F/L* 350mm(14") x 500mm(20") *Dantex AquaFlex Combination Unit*



- ~ User friendly digital control panel
- ~ Exposure/post-exposure drawer
- ~ Light integrator for optimum coverage
- ~ Computer controlled auto-reversing plateholder
- ~ Permanent adhesive plateholder fitted as standard
- ~ Time controlled pulsed hot air dryer
- ~ Suitable for stand-alone or plumbed installation
- ~ Operates from standard 13 amp electrical socket
- ~ De-tack drawer

For use with **Torelief & Toreflex** plates  
High Speed - High Quality - High Tech

# AquaFlex combination system for photopolymer plate making



## Specifications

### Power:

2.8Kw – 220/240 – 50/60 Hz

### Maximum plate size :

Dimensions: 350mm x 500mm  
14" x 20"

### Unit dimensions

865mm x 860mm x 1100mm (LxDxH)  
34" x 33.8" x 43.3"

### Net weight

110 kg / 243lb

### Operating weight

160 kg / 353lb

The information in this document is based on our present knowledge and experience. Due to the multitude of factors influencing the processing application of our products it does not release the user from own testing and experimentation.

Nor does it imply any legally binding assurance concerning specific properties of the products or suitability for a particular application. The responsibility of observing any pertinent industrial property rights, laws and regulations rests with the user. Subject to technical change without notice.

AQF - 500 E/EF

## Excellent Resolution Superb printed results

## Environmentally Friendly Water wash Processors



## High Quality – High Speed – High Tech